

KELAS	POWDER	AF 36	CO <sup>2</sup>	AF 11
<b>KELAS A</b>  Wood, Paper, Cloth, Trash & other ordinary material				
<b>KELAS B</b>  Gasoline, Oil, Paint, and other Flammable Liquids				
<b>KELAS C</b>  May be used on fires involving live electrical equipment without danger to the operator				



CE Certified Tube



CE Certified Valve



EN3 Certified Pressure Gauge



**Global Mitra Proteksindo**

Fire Protection and Safety Equipment

Head Office :

Komp. Perkantoran Taman Palem Mutiara  
 Blok A15 No. 28 Cengkareng, Jakarta Barat  
 Telp : 021 - 54353513, 54353488, 54353498  
 Fax : 021 - 54355904

Email : sales@globalmitraproteksindo.com  
 Website : www.globalmitraproteksindo.com

Factory & Workshop :

Jl. AMD Manunggal No. 99  
 Sepatan Timur, Tangerang  
 Telp. : (021) 5937100 (hunting)  
 Email : info@globalmitraproteksindo.com

**STARVVO™**  
 Fire Extinguisher



ISO / SNI ISO 9001:2008 Certified

PT. Global Mitra Proteksindo  
 Fire Protection and Safety Equipment

Dynamic Company's Management System has been Certified to ISO / SNI ISO 9001:2008



**STARVVO**™  
Fire Extinguisher

Your Partner  
in Fire Safety

Product Approval

CE  
0062

SNI



## Portable



Type	SV-10P	SV-20P	SV-30P	SV-30P	SV-50P	SV-60P	SV-12P
Kapasitas	1 Kg	2 Kg	3 Kg	3 Kg	5 Kg	6 Kg	12 Kg
Tinggi Tabung	75 cm	90 cm	90 cm	97 cm	97 cm	97 cm	97 cm
Diameter	52 cm	52 cm	52 cm	52 cm	52 cm	52 cm	52 cm
Working Pressure	15 - 18 Bar						
Test Pressure	27 Bar						
Berat Kosong	1.85 Kg	2.4 Kg	3.1 Kg	3.1 Kg	4.1 Kg	4.7 Kg	10.1 Kg
Pin Rating (UL Class 70B)	2A-10B	2A-10B	2A-10B	2A-10B	2A-10B	2A-10B	2A-10B
Effektivitas Pengapasan (%)	85%	85%	85%	85%	85%	85%	85%
Jarak Penyempitan (m)	2.7 m	2.8 m	2.8 m	2.8 m	3.1 m	3.1 m	4.1 m
Efektifitas Pemadatan	5 + 10 Detik						
Temperatur	20°C - 50°C						
Finishing	STICKER ANTI ROBEK						

## DRY CHEMICAL POWDER



## Trolley

Type	SV-200 P	SV-500 P	SV-750 P	SV-1500 P	SV-2000 P
Kapasitas	20 Kg	50 Kg	75 Kg	150 Kg	200 Kg
Tinggi Tabung	95.5 cm	97 cm	130 cm	110 cm	120 cm
Diameter	25 cm	38.5 cm	34 cm	54 cm	58 cm
Working Pressure	15 - 18 Bar				
Test Pressure	27 Bar				
Berat Kosong	54 Kg	97 Kg	132 Kg	180 Kg	240 Kg
Pin Rating (UL Class 70BC)	2A - 120B	30A - 125B	N/A	N/A	N/A
Effektivitas Pengapasan (%)	85%	85%	85%	85%	85%
Jarak Penyempitan (m)	9 m	10 m	12 m	12 m	14 m
Efektifitas Pemadatan	5 + 10 Detik				
Temperatur	20°C - 50°C				
Finishing	STICKER ANTI ROBEK				

## Portable



Type	SV-10L	SV-20L	SV-30L	SV-30L	SV-50L	SV-60L	SV-12L
Kapasitas	1 Kg	2 Kg	3 Kg	3 Kg	5 Kg	6 Kg	12 Kg
Tinggi Tabung	75 cm	90 cm	90 cm	97 cm	97 cm	97 cm	97 cm
Diameter	52 cm	52 cm	52 cm	52 cm	52 cm	52 cm	52 cm
Working Pressure	15 - 18 Bar						
Test Pressure	27 Bar						
Berat Kosong	1.85 Kg	2.4 Kg	3.1 Kg	3.1 Kg	4.1 Kg	4.7 Kg	10.1 Kg
Pin Rating (UL Class 70B)	2A-10B	2A-10B	2A-10B	2A-10B	2A-10B	2A-10B	2A-10B
Effektivitas Pengapasan (%)	85%	85%	85%	85%	85%	85%	85%
Jarak Penyempitan (m)	2.7 m	2.8 m	2.8 m	2.8 m	3.1 m	3.1 m	4.1 m
Efektifitas Pemadatan	5 + 10 Detik						
Temperatur	20°C - 50°C						
Finishing	STICKER ANTI ROBEK						

## LIQUID GAS STARVVO™ AF 36®



## Trolley

Type	SV-200 L	SV-500 L	SV-750 L	SV-1500 L	SV-2000 L
Kapasitas	20 Kg	50 Kg	75 Kg	150 Kg	200 Kg
Tinggi Tabung	95.5 cm	97 cm	130 cm	110 cm	120 cm
Diameter	25 cm	38.5 cm	34 cm	54 cm	58 cm
Working Pressure	15 - 18 Bar				
Test Pressure	27 Bar				
Berat Kosong	54 Kg	97 Kg	132 Kg	180 Kg	240 Kg
Pin Rating (UL Class 70BC)	2A - 120B	30A - 125B	N/A	N/A	N/A
Effektivitas Pengapasan (%)	85%	85%	85%	85%	85%
Jarak Penyempitan (m)	9 m	10 m	12 m	12 m	14 m
Efektifitas Pemadatan	5 + 10 Detik				
Temperatur	20°C - 50°C				
Finishing	STICKER ANTI ROBEK				





## STARVVO FOAM AFF 6%

Portable & Trolley

FOAM AFF 6%



Type	SV - 40 F	SV - 60 F	SV - 90 F	SV - 120 F	SV - 200 F	SV - 300 F
Kapasitas	4 Ltr	8 Ltr	9 Ltr	12 Ltr	20 Ltr	30 Ltr
Tinggi Tabung	21 cm	23 cm	26 cm	24 cm	90 cm	97 cm
Diameter	17,5 cm	19 cm	22,5 cm	22,5 cm	24 cm	26,5 cm
Working Pressure	15 - 18 Bar					
Test Pressure	27 Bar					
Berat Keseluruhan	3,1 Kg	10,1 Kg	13,7 Kg	17,7 Kg	68 Kg	87 Kg
Fire Rating (Lab. Dinas PAM)	6A - 20B	7A - 40B	10A - 60B	13A - 70B	2A - 120B	30A - 120B
Efektifitas Penyempitan (%)	85%	86%	88%	88%	88%	88%
Jarak Penyempitan (m)	3 - 10m	3 - 12m	4 - 14m	4 - 14m	5m	10m
Efektifitas Pemadaman	5 > 10 Detik					
Temperatur	20°C > 60°C					
Finishing	STICKER ANTI ROBEK					

## LIQUID GAS STARVVO™ AF 11®

Portable & Trolley

Liquid Gas STARVVO™ AF 11®  
(Clean Halon)



Type	SV - 10 AF	SV - 50 AF	SV - 120 AF	SV - 200 AF	SV - 350 AF	SV - 380 AF
Kapasitas	9 Kg	5 Kg	12 Kg	20 Kg	75 Kg	200 Kg
Tinggi Tabung	11,5 cm	21 cm	24 cm	90 cm	130 cm	130 cm
Diameter	11 cm	17,5 cm	22,5 cm	24 cm	24 cm	63 cm
Working Pressure	15 - 18 Bar					
Test Pressure	27 Bar					
Berat Keseluruhan	1,05 Kg	3,1 Kg	19,1 Kg	68 Kg	132 Kg	340 Kg
Fire Rating (Lab. Dinas PAM)	NA	NA	NA	NA	NA	NA
Efektifitas Penyempitan (%)	85%	85%	85%	85%	85%	85%
Jarak Penyempitan (m)	3-7m	3-11m	4-14m	5m	5m	10m
Efektifitas Pemadaman	5 > 10 Detik					
Temperatur	20°C > 60°C					
Finishing	STICKER ANTI ROBEK					

## CARBON DIOXIDE (CO<sup>2</sup>)

Portable & Trolley

Carbon Dioxide (CO<sup>2</sup>)



Type	SV - 230 C	SV - 320 C	SV - 460 C	SV - 680 C	SV - 2300 C	SV - 4500 C
Kapasitas	2,3 Kg	3,2 Kg	4,6 Kg	6,8 Kg	23 Kg	45 Kg
Tinggi Tabung	20,5 cm	27 cm	27 cm	33 cm	55 cm	164 cm
Diameter	14,9 cm	14,9 cm	19,5 cm	19,5 cm	29 cm	29 cm
Working Pressure	20 - 30 Bar					
Test Pressure	40 Bar					
Berat Keseluruhan	8,2 Kg	9,5 Kg	16 Kg	21 Kg	98,5 Kg	147,5 Kg
Fire Rating (Lab. Dinas PAM)	2B	3B	3B	4B	7B	10B
Efektifitas Penyempitan (%)	96%	96%	97%	97%	90%	90%
Jarak Penyempitan (m)	3 - 6m	3 - 6m	4 - 7m	4 - 7m	7m	8m
Efektifitas Pemadaman	5 > 10 Detik					
Temperatur	20°C > 60°C					
Finishing	STICKER ANTI ROBEK					